



## Arctic Low Pour Hydraulic Oil

Arctic Low Pour Hydraulic Oil is a high-quality, low-viscosity antiwear hydraulic oil specially developed for use in industrial and mobile equipment operating at extremely low temperatures. It has a very high viscosity index and low pour point for use in arctic conditions.

Arctic Low Pour Hydraulic Oil is formulated to provide outstanding low-temperature properties, good wear protection for hydraulic pumps and motors, resistance to deposit formation, and protection against rust and corrosion. It has good water-separating properties to minimize the formation of emulsions, and is resistant to excessive foam buildup that can cause poor or sluggish hydraulic system response.

Arctic Low Pour Hydraulic Oil may be used in land-based hydraulic systems where the equipment manufacturer specifies a MIL-H-5606 fluid. It is **not** recommended for aircraft use.

### Applications

- Industrial and mobile equipment operating in cold climates
- Bucket trucks (cherry pickers) used for servicing electrical power lines or for tree trimming
- Surface mining equipment

### Features/Benefits

- Outstanding low-temperature properties
- Very high viscosity index for use in arctic conditions
- Good wear protection for hydraulic pumps and motors
- Resists deposit formation and viscosity increase due to oxidation
- Protects against rust and corrosion
- Good water-separating properties
- Good foam resistance
- High dielectric strength for use in electrical service bucket trucks (cherry pickers)<sup>(1)</sup>

<sup>(1)</sup> **Note:** In order to maintain its high dielectric strength for use as electrical insulating oil, the oil must be kept clean and dry. Contamination with water will significantly decrease the dielectric strength.

**Low-Pour, High VI  
Antiwear Hydraulic  
Oil For Cold  
Climates**

Customer Service  
Number:  
**1-714-556-0808**

Email Address:  
Anthony@  
Intraoil.com



### Arctic Low Pour Hydraulic Oil

#### Typical Properties

<b>ISO Grade</b>	<b>15</b>
Specific Gravity @ 60°F	0.876
Density, lbs/gal @ 60°F	7.29
Color, ASTM D1500	0.5
Flash Point (COC), °C (°F)	103 (217)
Pour Point, °C (°F)	-60 (-76)
Viscosity,	
cP @ -40°C (Brookfield)	450
cSt @ -40°C (calculated)	226
cSt @ 40°C	15.0
cSt @ 100°C	5.6
SUS @ 100°F	80.3
SUS @ 210°F	44.9
Viscosity Index	377
Dielectric Strength, ASTM D877, kv <sup>(2)</sup>	35
Demulsibility, ASTM D1401, minutes to pass	30
Foam Test, ASTM D892	Pass
Four-Ball Wear, ASTM D4172, Scar Diameter, mm	0.66
Rust Test, ASTM D665 A&B	Pass
Zinc, wt %	0.050

<sup>(2)</sup> At the point of manufacture

#### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2010 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.