



## DEXRON®-VI ATF

Kendall® DEXRON®-VI ATF is a next-generation, synthetic transmission fluid approved for use in passenger car and light truck automatic transmissions that require a GM DEXRON®-VI or earlier-generation DEXRON® fluid. It provides significantly improved oxidation stability, shear stability, friction durability and foam resistance compared with earlier generation DEXRON® fluids.

DEXRON®-VI ATF is specifically engineered to help ensure long service life, provide better performance under extreme operating conditions, and provide consistent shift performance for the life of the fluid. It is particularly recommended for use in new GM 6-speed automatic transmissions, and is fully backwards compatible for use in older GM automatic transmissions.

### **Applications**

- Service fill in all automatic transmissions that require a GM DEXRON®-VI or earlier-generation DEXRON® transmission fluid
- Hydraulic systems on industrial and mobile equipment operating over a wide temperature range

DEXRON®-VI ATF meets or exceeds the requirements of:

- GM DEXRON®-VI
- Denison Hydraulics HF-0
- Vickers (Eaton) M-2950-S, I-286-S

### **Features/Benefits**

- Meets stricter performance requirements for new GM 6-speed automatic transmissions
- Outstanding friction durability for consistent shift performance for the life of the fluid
- Excellent oxidation resistance and thermal stability for long fluid life
- Protects against sludge and varnish formation
- Protects against wear
- Protects against rust and corrosion
- High shear stability
- Excellent low-temperature properties
- Good seal compatibility
- Good foam resistance
- Backwards compatible for use in older GM automatic transmissions

**GM DEXRON®-VI  
Automatic  
Transmission Fluid**

Customer Service  
Number:  
**1-714-556-0808**

Email Address:  
Anthony@  
Intraoil.com

**DEXRON®-VI ATF****Typical Properties**

Specific Gravity @ 60°F	0.845
Density, lbs/gal @ 60°F	7.03
Color, Visual	Red
Flash Point (COC), °C (°F)	229 (444)
Pour Point, °C (°F)	<-45 (<-49)
Viscosity, Brookfield	
cP @ -40°C	11,500
Viscosity, Kinematic	
cSt @ 40°C	29.8
cSt @ 100°C	6.0
Viscosity Index	151
Zinc, wt %	<0.002

**Health and Safety Information**

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2009 ConocoPhillips Company. ConocoPhillips, Kendall, their respective logos, the Two Finger logo, and Liquid Titanium are trademarks of the ConocoPhillips Company in the U.S.A. and other countries.