



Super HD II Motor Oil

Super HD II Motor Oil is a high-quality universal fleet engine oil designed for use in on-highway diesel trucks and off-highway diesel equipment, as well as in passenger cars and light trucks with either diesel or gasoline engines. It is recommended for use both in EGR-equipped diesel engines and in older, non-EGR diesel engines. It also will provide excellent protection for gasoline engines for use in mixed commercial fleets.

Super HD II is formulated with advanced additive technology to provide excellent wear protection, soot control and bearing corrosion protection. It has excellent soot dispersancy to protect against abrasive wear and soot-induced oil thickening, and excellent oxidation resistance to help minimize deposit formation.

Super HD II meets or exceeds the performance requirements of API Service Categories CI-4 and SL, API CI-4 PLUS and leading OEM specifications for diesel engine oils.

Applications

- On-highway diesel trucks equipped with cooled-EGR, ACERT or other technologies to meet 2004 and earlier exhaust emission standards
- Older diesel equipment with conventional, non-EGR engines
- Mixed fleets with both diesel and gasoline-fueled vehicles
- Off-highway construction, earth moving and mining equipment
- Farm equipment with diesel or gasoline engines

Super HD II meets or exceeds the requirements of:

- API Service CI-4 with CI-4 PLUS, CI-4, CH-4, SL
- Caterpillar ECF-2, ECF-1a
- Cummins CES 20078, CES 20076
- Mack EO-N Premium Plus 03
- Volvo VDS-2
- Diesel engines manufactured by OEMs not listed above, including Detroit Diesel, International (Navistar), John Deere, Hino, Komatsu, Kubota and others

Features/Benefits

- Excellent soot control for protection against abrasive wear and soot-induced oil thickening
- Resists viscosity and thermal breakdown at high temperatures

Universal Fleet Engine Oil

Customer Service
Number:
1-714-556-0808

Email Address:
Anthony@
Intraoil.com



- Protects against sludge and varnish formation
- Protects against wear
- Protects against rust and bearing corrosion
- Good low-temperature pumpability, even with soot-laden oil
- Good resistance to foaming and aeration

Super HD II Motor Oil

Typical Properties

SAE Grade	15W-40
Specific Gravity @ 60°F	0.878
Density, lbs/gal @ 60°F	7.31
Color, ASTM D1500	L 4.0
Flash Point (COC), °C (°F)	232 (450)
Pour Point, °C (°F)	<-36 (<-33)
Viscosity, Kinematic	
cSt @ 40°C	113
cSt @ 100°C	15.0
Viscosity Index	135
Cold Cranking Viscosity, cP	6,500
@ (°C)	(-20)
High-Temp/High-Shear Viscosity, cP @ 150°C	4.1
Sulfated Ash, ASTM D874, wt %	1.18
Total Base Number (TBN), ASTM D2896	9.5
Zinc, wt %	0.134

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2010 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.